



# Your Effective Deterrent Against Intruders



1/1.8" Image Sensor



Clear B&W Images (Cofocal Lens)



Multi-Core Illuminators



Lens Distortion Correction



Dual-Power Backup

### | What is TiOC PRO?

The new TiOC PRO series features significant enhancements across its hardware and functionality, including an upgraded image sensor and a more powerful dual-illuminator system for longer illumination distances. Image improvements include extended illumination distances and the LDC function, alongside dual-power backup for increased reliability.



#### **TiOC PRO Bullet (8MP/6MP)**

- IPC-HFW3849T1P-AS-PV-0280B-PRO / 0360B-PRO
- IPC-HFW3649T1P-AS-PV-0280B-PRO / 0360B-PRO

#### **TiOC PRO Turret (8MP/6MP)**

- IPC-HDW3849HP-AS-PV-0280B-PRO / 0360B-PRO
- IPC-HDW3649HP-AS-PV-0280B-PRO / 0360B-PRO








# 1/1.8" Image Sensor

- A large 1/1.8" image sensor provides better image quality and clarity.
- Increasing the sensor area by 110% creates brighter images with less noise.





# $\overline{Q}$

#### AcuPick

 Utilises a deep learning algorithm and collaborates with back-end devices to precisely match targets, such as people and vehicles, enabling efficient searches through live and recorded videos to quickly locate targets.



# **Built-In Dual Mic & Speaker**

- Offers better noise reduction and two-way audio.
- The red and blue light flashes while the siren makes a warning sound to deter intruders.
- Customisable alert voice audio.





# Al Coding ABR (Average Bit Rate)

• Al Coding offers three rate control strategies: ABR, CBR, and VBR, effectively enhancing image quality and conserving bandwidth to accommodate diverse scenarios.





### LDC & Dual-Power Backup

- Lens Distortion Correction enables more accurace images by reducing disfigurement.
- PoE / 12v DC dual-power backup.







# **Smart Dual-Light**

• The cameras illumination can be adjusted according to the time of day, enhancing configuration efficiency and suiting more scenario applications with Smart Illumination Mode, Warm Light Mode, and IR Mode.





# **Smart Motion Detection (SMD4.0)**


- Filters out false alarms and focuses on human and vehicle targets.
- False alarm rate < 1%.
- Sends alarms only when a person or vehicle has been detected for intrusion.





### **Perimeter Protection**

- Based on tripwire and area intrusion rules, this feature sends an alarm when unwanted movements by people or vehicles are detected, therefore avoiding unnecessary false alarms.
- False alarm rate < 1%.





## AI-SSA (AI Scene Self-Adaption)

• Utilises artificial intelligence and a deep-learning algorithm to identify various scenes and adjusts accordingly, ensuring images are optimised to suit the conditions.







# | Product Specification

Image Sensor	1/1.8" CMOS
Min. Illumination	0.0008 Lux@F1.0 (Colour, 30IRE); 0.0004 Lux@F1.0 (B/W, 30IRE); 0 lux (Illuminator on)
Illumination Distance	Bullet: Up to 50 m (IR & Warm Light); Turret: Up to 30 m (IR & Warm Light)
Illuminator	4 Multi-Core Light (IR + Warm)
Field of View	2.8 mm: H: 109°; V: 59°; D: 131°; 3.6 mm: H: 93; V: 50°; D: 111°
Video Frame Rate	Main-stream: 3840×2160 @(1 fps-25/30 fps); Sub-stream: 1920×1080@ (1 fps-25/30 fps); Third-stream: 1920×1080@ (1 fps-25/30 fps)
Bit Rate Control	CBR, VBR & ABR
Privacy Masking	8 Areas (Colour Block) or 4 Areas (Mosaic)
Temperature	-40 °C to +60 °C
Built-in Mic	Dual-Mic
AcuPick	Supported
<b>Active Deterrence</b>	Red & Blue Warning Lights & Sound Alarm
Dual-Power Backup	PoE & DC12V Dual-Power Backup

Dahua UK & Ireland (Head Office) 3rd Floor, Quantum, 60 Norden Road,

Maidenhead, Berkshire SL6 4AY

sales.uk@dahuatech.com Tel: support.uk@dahuahelp.com +44 (0) 1628 200 880









