



Doorbell 2S Kit

2K Wire-Free Video Doorbell


With 3MP/2K live monitoring, ultra wide-view lens with 30° pan features, Doorbell 2S ensures every corner in front of door completely covered. With 5000mAh rechargeable battery, Doorbell 2S is 100% wire-free, waterproof and easy to install. PIR, AI human detection and loitering detection quickly find targets and immediately sends a notification to you. Doorbell 2S supports to talk with variable voice and customizable quick voice reply to protect your privacy. Indoor Chime DS2S works as a Wi-Fi extender and a local storage, providing stable network for the doorbell and upgraded protection for the recorded footage.





Stay close with what you care

With Cloud service, you will have access to what you care as long as Internet is available. You can record daily or motion videos on Cloud and play back anytime anywhere.



Specifications

Video Doorbell

1/2.8" Progressive CMOS
3MP (2048 x 1536)
Night Vision: 5m(16.5ft) Distance
2.3 mm Fixed Lens, 30° Pan
Field of View : 125° (H), 98° (D), 166° (D)
5000mAh Rechargeable Battery

Video & Audio

Video Compression : H.265 Up to 15fps Frame Rate Two-way Talk 8x Digital Zoom

Notice Management

Doorbell Call Notification PIR Motion Detection Loitering Detection Auto Power Saving Mode

Network

Wi-Fi:IEEE802.11b/g/n, 2.4GHz Chime works as the Wi-Fi extender for the Doorbell imou App: iOS, Android


What's in the box

- 1x Doorbell
- 1x Quick Start Guide
- 1x Surface Mounting Bracket
- 1x USB Charging Cable
- 3x Wire Nuts
- 2x 3M Glue
- 1x Chime Plug

- 1x Pin - 1x Installation Position Map

- 1x Screw Package

- 2x Extension Wire
- 1x Jumper Wire
- 1x Chime



Auxiliary Interface

Video Doorbell: Built-in Mic & Speaker Power On / Off Button

Chime: Micro SD Card Slot (up to 512GB) Built-in Speaker Reset Button

General

Video Doorbell: Charging Power: DC 5V 1A, Type-C Port Optional Hardwired Power Supply (8~24VAC, \geq 5VA) Power Consumption: up to 2.27W Working Environment:-20° C~+50° C, Less Than 95%RH Charging Temperature:0° C~+45° C Dimensions: 150 × 55 × 50.3 mm (5.9 × 2.2 × 2.0 inch) Weight: 237.5g (0.5 lb) CE, Weatherproof

Chime:

AC Power Supply: 100-240 VAC Power Consumption: up to 3W Working Environment: -10° C $-+45^{\circ}$ C, Less There 95% RH Dimensions: $95.5 \times 65.1 \times 30.2$ mm ($3.8 \times 2.6 \times 1.2$ inch) Weight: 79g (0.2 lb) CE