



TSC 20 Fibre patch cord 20m SC

Art. Number 307014



Fibre Optic patch cord

The **TSC xx patch cord** is a single mode cable terminated with SC/APC connector plugs at both ends. It is recommended for indoor installations in cable ducts and cabinets of fibre optic networks used for applications like:

- CATV distribution and DOSIS data transmission
- SAT-IF and DTT distribution
- Other fibre optic communication systems

Technical Specifications

ORDER INFORMATION

EAN Number 5702663070141

OPTICAL CHARACTERISTICS

Optical Attenuation 1310/1550 | dB/km 0.3 dB/km
Optical cabletype Single-mode
Fibre type G.652.D

CONSTRUCTION

Jacket - material LSZH
Jacket - dimension | mm 3.0 mm

CHARACTERISTICS

Wavelength | nm 1310...1550 nm

RETURN LOSS

Return Loss | dB >60 dB

OPERATIONAL

Temperature - operating | °C -40...+80 °C

CONNECTORS

Connector Type Optical - SC/APC



Technical Specifications

MECHANICAL

Minimum bending radius mm	50 mm
Cable length m	20 m
Colour	Yellow
Packaging Height m	0.000 m
Packaging Width m	0.000 m
Packaging Depth m	0.000 m
Packaging Volume m ³	0.000 m ³
Net Weight kg	0.420 kg
Tara Weight kg	0.003 kg
Total Weight kg	0.423 kg