

9-30783

AirSense ModuLaser, Detector module

General

ModuLaser is a scalable aspirating smoke detection solution that makes installation easier, maintenance quicker, and takes applications further than traditional air sampling detectors. Two basic module types comprise

the ModuLaser solution: a display module, and a detector module.

Each detector module can accommodate up to 250 meters combined sampling pipe. Display modules and detector modules communicate by RS-485 interconnections.

Display modules are available in three configurations: Standard with TFT color display, status LED's and navigation buttons, Minimum with only status LED's, and Command which is similar to the Standard but with the added functionality to control various modules over SenseNET. The Minimum and Standard Display Modules can each support up to 8 detector modules, while the Command Display Module can support up to 127 modules across the SenseNET network.

Detector module

The Detector Module is a fully self-contained unit, which aspirate the sampled air from the protected area, analyze the air and based on ClassiFire determine if a pre-alarm or alarm should be raise, if smoke particles would be present in the sampled air. If an alarm condition or fault condition would occur, then the unit will activate the corresponding local relay output, subjected to the programming of the relays. Simultaneously the alarm or fault condition would also be reported to the Display Module to which the Detector Module is connected.

Due to the modular nature of the ModuLaser, maintenance (for example routine filter replacement) can be done on a module per module bases, rather than a complete system. This in turn reduces the risk of the area which is unprotected during the maintenance period, as only one sampling pipe (protected zone) would be affected at a time.

Perfect solution

Thanks to advanced features that make it virtually impervious to dust and dirt, ModuLaser is ideal for use in hostile environments that would disable other kinds of smoke detectors. Forward scattering optical detection adds early warning capability without the risk of nuisance alarms normally associated with high sensitivity smoke detection, while exclusive environmental compensation technology adds a high degree of reliability to an already solid detection solution.



Details

- Modular Design : Separate centrally-controllable detector modules allow efficient piping and discrete zones with no overlap.
- Zoned aspirating smoke detection : Individual detector modules provide detection for individual areas or zones, specific zone alarm information can be transmitted to the main fire alarm panel via a common APIC address card in the display module or through dedicated alarm relays within each detector module.
- Simplified installation : Ingenious docking station design allows detectors to be easily connected together as a group. Sensitive electronics are easily removed to ensure they will not be damaged during first fix installation. Aspirating pipework and cable entries can easily be made into either the top or the bottom of the unit.
- Intuitive user interface : Bright easy-to-see color TFT display and universal navigation and control buttons take the guesswork out of programming and diagnostics.
- Easy pipe connection : The quick fit pipe adaptor system locks down securely, yet leaves plenty of room for easy pipe connection and removal.
- Quick location of smoke : Each detector module is self-contained, which means no delays in determining in which zone (sampling pipe) smoke is present.

9-30783

AirSense ModuLaser, Detector module

Technical specifications

General

Status indication	LED's
User interface	TFT and navigation buttons on Normal and Command Display Modules
Alarm levels	4 (Aux, Pre-alarm, Alarm and Alarm 2)
Event log	20 000 events per module
RS485 support	Yes (SenseNET and SenseNET+)
Connectivity	USB (x2), IP and APIC on Display Module

Electrical

Operating voltage	18 to 30 VDC
Current consumption	Display Module (at 24 VDC): 204 mA - Minimum Display Module 232 mA - Standard Display Module 232 mA - Command Display Module Detector Module (at 24 VDC): 260 mA - fan speed 1 380 mA - fan speed 6 (default speed) 940 mA - fan speed 16

Detection

Detection principle	Laser light scattering mass detection and particle evaluation
Sensitivity	0.002 %obs/m to 25 %obs/m (0.0006 %obs/ft to 7.62 %obs/ft)
Particle sensitivity range	0.003 to 10 microns

Sampling pipe

Length	Up to 250 m (820 ft.) combined per detector module
Quantity sampling holes	Up to 20 - Class A per detector module Up to 40 - Class B per detector module Up to 50 - Class C per detector module
Inlet size	27 or 25 mm (1.06 or 0.98 in) outer diameter
Inlet location	Top or bottom
Exhaust size	27 or 25 mm (1.06 or 0.98 in) outer diameter
Exhaust location	Top or bottom
Inlet quantity	1 per detector module

Input

Input quantity	2 per module
Input type and rating	Supervised
Termination	15 K Ω 5% 1/4 W
Programmable	Yes

Output

Output quantity	3 per module
Output type and rating	Voltage free (contact rating 2 A at 30 VDC / NO/NC/C)
Programmable	Yes

Physical

Physical dimensions	W x D x H 110.5 x 133.5 x 300 mm (4.35 x 5.25 x 11.8 in)
Net weight	Display Module: 1.18 Kg (2.6 lb.) Detector Module: 1.57 Kg (3.46 lb.)
Colour	Cream
Mounting type	Surface mount
Cable entries	2 at the bottom, 2 at the rear, 2 at the top on Detector Module, and 3 at the top on the Display Module
Cable entry size	20 mm (0.5 in) - top and bottom
Detector module orientation	Vertical (0 deg or 180 deg)

Environmental

Operating temperature	Equipment: -20 to +60 °C (-4 to +140 °F) Sampled air: -20 to +60 °C (-4 to +140 °F)
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP40

Regulatory

Compliance	REACH, RoHS
Certification	BOSEC, CPR, CSIRO, EN54-20, LPCB, VdS

Chart recorder

Sampling period	Adjustable between 1s and 60 s
Capacity	1 months @ 1s / Up to 5 years @ 60 s
Values recorded	Detector value, 4 alarm level values, flow value and temperature (all simultaneously)

Compatible products

Category	Reference	Description
Detection device	9-30780	AirSense ModuLaser, Minimum Display Module
Detection device	9-30781	AirSense ModuLaser, Standard display module
Detection device	9-30782	AirSense ModuLaser, Command display module



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 17 September 2024 - 14:13